

PAVESEAL

PAVING FABRIC

TECHNICAL DATASHEET	G 030 006
ISSUE NUMBER	07
DATE	OCTOBER 2021

CHARACTERISTIC	TEST STANDARD	UNITS	AS240P	AS280P
TENSILE PROPERTIES				
Grab Strength	AS 2001.2.3	N	500	700
Elongation	AS 3706.4	%	> 40	> 40
Grating	Austrroads	-	900	1350
PHYSICAL PROPERTIES				
Polymer		-	Polyester	Polyester
Melting Point		°C	> 230	> 230
Standard Roll Size		m	4 x 100	4 x 100
Nominal Roll Weight		kg	60	77



Controls established by Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ 001784-1

DISCLAIMER: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd have a policy of continuous development so information and product specifications may change without notice.

0800 CIRTEX (247 839) | WWW.CIRTEX.CO.NZ

