

# AQUADUCT

Flexible Flume

TECHNICAL DATASHEET	G 012 001
ISSUE NUMBER	04
DATE	JULY 2020

PROPERTIES	VALUES
Weight	600gsm
Basic Cloth	Polyester 550 Decitex
Weave	8 x 8 per cm
Coating	PVC paste coated
Surface Finish	High gloss ROWACRYL protective finish
Uv Stabilisation	AS2001.4.21
Tear Strength	250/200N
Tensile Strength	1100/840N
Adhesion	90N/50mm minimum
Flexing	400,000 cycles minimum / AS.1441.6

#### DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.



This product has been manufactured under the controls established by a Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ001832-2

0800 CIRTEX (247 839) | [WWW.CIRTEX.CO.NZ](http://WWW.CIRTEX.CO.NZ)

