BIOCOIR BC450JR

Coconut Matting

| TECHNICAL DATASHEET | G 036 010 |
|---------------------|--------------|
| ISSUE NUMBER | 04 |
| DATE | JANUARY 2020 |

Description

Cirtex BioCoir is a biodegradable coconut fibre matting for erosion and sediment control and landscaping applications. Cirtex BioCoir is ideal for protecting cut faces and exposed soil from erosion from wind and water. In addition to the erosion control function, Cirtex BioCoir allows moisture penetration to assist vegetation establishment while insulating the seed and root zones from extremes of heat.

Applications

- Steepened slopes
- Road, rail and sound barrier embankments
- Low flow stormwater channels
- Highly erodible soils
- Heavy rainfall areas
- Parks, Amenity areas, Golf courses and Sports grounds

Installation

Prepare the ground by clearing away any rocks and debris and level as much as possible to ensure the BioCoir will have good ground contact. On slopes, anchor the matting in a 150mm trench at the top of the slope and roll down the slope, overlapping rolls by 100mm. Pin the BioCoir to the ground with ground pins or 230mm Ground Staples, using 1 pin/staple per m² on flat and gentle slopes, and up to 4 pins/staples per m² on steeper slopes. BioCoir can be hydroseeded if required.

TYPICAL PROPERTIES

| PROPERTY | BIOCOIR BC450JR |
|------------------------|--|
| Material | Coir Fibre, Jute Net and Cotton Thread |
| 100% Biodegradeable | |
| Thickness (Nominal) | 7mm |
| Mass (g/sqm) (Nominal) | 450gsm |
| Dimensions | 2.4m x 50m |



This product has been manufactured under the controls established by Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ 001784-1



DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.

0800 CIRTEX (247 839) | WWW.CIRTEX.CO.NZ