

BioCoir BC300JR

COCONUT MATTING

TECHNICAL DATA SHEET	TDS G 001 114
ISSUE NUMBER	01
DATE	JANUARY 2020

DESCRIPTION

Cirtex BioCoir is a biodegradable coconut fibre matting for erosion and sediment control and landscaping applications. Cirtex BioCoir is ideal for protecting cut faces and exposed soil from erosion from wind and water. In addition to the erosion control function, Cirtex BioCoir allows moisture penetration to assist vegetation establishment while insulating the seed and root zones from extremes of heat.

APPLICATIONS

- Steepened slopes
- Road, rail and sound barrier embankments
- Low flow stormwater channels
- Highly erodible soils
- Heavy rainfall areas
- Parks, Amenity areas, Golf courses and Sports grounds

INSTALLATION

Prepare the ground by clearing away any rocks and debris and level as much as possible to ensure the BioCoir will have good ground contact. On slopes, anchor the matting in a 150mm trench at the top of the slope and roll down the slope, overlapping rolls by 100mm. Pin the BioCoir to the ground with ground pins or 230mm Ground Staples, using 1 pin/staple per m² on flat and gentle slopes, and up to 4 pins/staples per m² on steeper slopes. BioCoir can be hydroseeded if required.

TYPICAL PROPERTIES

PROPERTY	BIOCOIR BC300JR
MATERIAL	Coir Fibre, Jute Net and Cotton Thread
100% BIODEGRADABLE	
THICKNESS (Nominal)	4mm
MASS (g/sqm) (Nominal)	300gsm
DIMENSIONS	2.4m x 50m

DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.



ISO 9001:2015
Reg.No: C41186