


# TERRADRAIN

## WD250

TECHNICAL DATA SHEET	G 035 002
ISSUE NUMBER	01
DATE	MARCH 2020

### Product Description

TerraDrain (Prefabricated Vertical Drain or Wick Drain) is designed for expediting consolidation of slow draining soils. TerraDrain has a unique continuous corrugated plastic core encased with a durable geotextile.

PHYSICAL PROPERTIES	STANDARD	UNIT	SPECIFICATIONS
Core Type			Fish Bone Corrugations
Core Configuration			
Width	ASTM D-3774	mm	100 ± 5.0
Thickness	ASTM D-5199	mm	3.3 ± 0.5
Material			PP/PET
<b>HYDRAULIC PROPERTIES DRAIN</b>			
Discharge Capacity (300 kPa i = 1.0)	ASTM D-4716	m <sup>3</sup> /yr	>3150
<b>MECHANICAL PROPERTIES</b>			
Grab Tensile Strength (Filter)	ASTM D-4632	kN	0.3 ± 0.05
Tensile Strength (Assembled Drain)	ASTM D-4595	kN/Full Width	>2.5 ± 0.3
<b>HYDRAULIC PROPERTIES FILTER</b>			
Opening Size O <sub>90</sub>	ASTM D-4751	µm	<80
Permeability	ASTM D-4491	m/s	>2 x 10 <sup>-4</sup>

### DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.

ISO 9001

BUREAU VERITAS  
Certification



This product has been manufactured under the controls established by a Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ001832-2