

Strol

SurePave™

Data Sheet

G 046 001

Issue No.: 01

September 2020



SurePave™

Permeable Paving

Technical Data Sheet	G 046 001
Issue Number	03
Date	September 2019

Technical Specifications*

Structure	Interlocking Open Structure Hollow Pavers
Locking System	Positive Lock Clipping System
Panel Dimensions	816mm x 612mm x 40mm
Material	Polypropylene Recycled
Unit Weight	2kg
Crush Strength Unfilled	>133 tonnes/m ²
Crush Strength Filled With Stone	>740 tonnes/m ²
Test Methods	Compression, NZS 3116 : 1991, App A & B
Maximum Recommended Gradient	≤ 11 degrees

- The listed technical values are guiding values, achieved in our laboratories and/or independent testing institutes. Our products are subject to changes without prior notice.

+61 2 9066 6716 / STROL.COM.AU

Strol



This product has been manufactured under the controls established by Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ 001784-1

DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Strol Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Strol Ltd has a policy of continuous development so information and product specifications may change without notice.