

# PEBBLELOCK

## PERMEABLE PAVING

<b>TECHNICAL DATA SHEET</b>	TDS G 001 165
<b>ISSUE NUMBER</b>	01
<b>DATE</b>	JUNE 2020

### TECHNICAL SPECIFICATIONS

STRUCTURE	Mesh backed open structure octagonal hollow cell paver
LOCKING SYSTEM	Positive lock clipping system
PANEL DIMENSIONS	840mm x 590mm x 24mm
CELL SIZE	55mm
CELL WALL THICKNESS	Tapered 2.0mm - 2.4mm (top-bottom)
COVERAGE	0.5m <sup>2</sup>
MATERIAL	Polypropylene recycled
UNIT WEIGHT	1.15kg
WEIGHT/m <sup>2</sup>	2.30kg
CRUSH STRENGTH UNFILLED	180 tonnes/m <sup>2</sup>
CRUSH STRENGTH FILLED WITH STONE	300 tonnes/m <sup>2</sup>
TEST METHODS	Compressive strength test
MAXIMUM RECOMMENDED GRADIENT	≤ 11 degrees
UV & FROST	UV and frost resistant
COLOUR	Black
MANUFACTURING LOCATION	Australia

ISO 9001

BUREAU VERITAS  
Certification



This product has been manufactured under the controls established by Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ 001784-1

The listed technical values are guiding values, achieved in our laboratories and/or independent testing institutes. Our products are subject to changes without prior notice.

#### DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.

