

The Strol logo is written in a bold, white, italicized sans-serif font on a blue background.

***Strol***

# PebbleLock

## Data Sheet

G 129 001

Issue No.: 01

September 2020



# PebbleLock

## Permeable Paving

Technical Data Sheet	G 129 001
Issue Number	01
Date	June 2020

### Technical Specifications\*

Structure	Mesh backed open structure octagonal hollow cell paver
Locking System	Positive lock clipping system
Panel Dimensions	840mm x 590mm x 24mm
Cell Size	55mm
Cell Wall Thickness	Tapered 2.0mm - 2.4mm (top-bottom)
Coverage	0.5m <sup>2</sup>
Material	Polypropylene recycled
Unit Weight	1.15kg
Weight/M <sup>2</sup>	2.30kg
Crush Strength Unfilled	180 tonnes/m <sup>2</sup>
Crush Strength Filled With Stone	300 tonnes/m <sup>2</sup>
Test Methods	Compressive strength test
Maximum Recommended Gradient	≤ 11 degrees
UV & Frost	UV and frost resistant
Colour	Black
Manufacturing Location	Australia

- The listed technical values are guiding values, achieved in our laboratories and/or independent testing institutes. Our products are subject to changes without prior notice.

+61 2 9066 6716 / [STROL.COM.AU](http://STROL.COM.AU)

# Strol



This product has been manufactured under the controls established by Bureau Veritas certification approved management system that conforms with ISO 9001:2015. Bureau Veritas Certification certificate number NZ 001784-1

#### DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Strol Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Strol Ltd has a policy of continuous development so information and product specifications may change without notice.